AMENDMENT TO THE SPECIFICATIONS

Insert new paragraphs 56 and 57 and renumber paragraph 56 to 58. The contents of renumbered paragraph 58 remain unchanged. New paragraph 56 describes new drawings Figs. 8a and 8b. New paragraph 57 describes new drawing Fig. 9.

section 401 and a second section 402. The first end of first section 401 has spiral grooves. In this embodiment, the spiral grooves on the first end of first section 401 may be configured so that when first section 401 is inserted into support base 403 the first end is attached to nut 404. The second end of first section 401 may also have spiral grooves that allow first section 401 to be coupled to second section 402. FIG. 8B shows an angular view of a two piece arm having a first section 501 and a second section 502. Support base 503 has a hollow cylindrical column with grooves that correspond to the spiral grooves on the first end of first section 501. These grooves allow first section 501 to be attached to support base 503. To provide a more secure attachment, nut 504 may also be used for attachment purposes.

FIG. 9 shows an angular view of a two piece arm with a first section 601 and a second section 602. The first end of first section 601 has spiral grooves and the second end includes a hinged coupling means 605. Hinge 605 provides a means by which the arm can be easily folded. Nut 604 may be included as an attachment means that secures first section 601 to support base 603.

0056 0058 As was shown in the figures and description, this accessory hanger has several embodiments that make it very useful. It has a variety of support bases, arms and attachment means that are interchangeable. Although certain preferred embodiments of this invention have been described, the spirit and scope of the invention is not limited to what is described above.